

HP-200 Torque Tester



Introduction

Torque tester HP-200 is a bottle cap locking and opening torque value testing instrument developed and manufactured by the GBPI Research and Development Team based on ASTM and GB standard requirements and market demand. For bottled packaging products, nozzle packaging products and tube packaging products, the opening torque of the bottle cap is one of the key control process parameters, which has a great impact on the intermediate transportation and final consumption of the product.

It is a dedicated equipment for measuring the locking and opening torque of bottled products, and it is an indispensable test equipment in the production process.

Standard

ASTM D 2063, ASTM D 3198, ASTM D 3474, GB/T 17876, BB/T 0025, BB/T 0034(GB/T 14803)

Specification

Item	Technical Parameters
Test range	0~20 N·m
Test accuracy	0.5 grade
Resolution	0.001 N·m
Clamping range	Ф5~230mm
Statistics	10 groups
Power supply	AC220V 50Hz
Dimensions	317mm*395mm*208mm
Net weight	About 5 KG

Features

- ◆ High-definition LCD screen display, the torque value is the torque number, which is easy and accurate to read.
 - It has data tracking and holding functions.
- lack Three sets of torque unit switching functions: Lbf \cdot in (pound force \cdot inch), Kgf \cdot cm (kg \cdot cm), N \cdot m (Newton \cdot meter).
- ◆ The tester can be used to measure the torque in the clockwise direction and the counterclockwise direction, which can be used as the torque of the tightened part and the loosened part.

Application

	bottled container	It is suitable for the torque value test of bottle cap locking and opening of bottled packaged food and medicine (threaded connection), such as beverage bottles, medicine bottles, etc.
	Vacuum bottles and mugs	It is suitable for the torque value test of the locking and opening of the bottle caps of thermos bottles and thermos cups (threaded connection).
VOO COMMANDE OF THE PARTY OF TH	Spout pouches	It is suitable for the torque value test of bottle cap locking and opening for nozzle packaging products.
	Soft tube products	It is suitable for the torque value test of bottle cap locking and opening for tube packaging products.

Factory configuration

Standard	Host, fixture, buffer force accessories
configuration	Host, fixture, buffer force accessories

Note: GBPI has always been committed to the innovation and improvement of product performance and function. For this reason, product technical specifications and appearance will also be changed accordingly. The above situation will not be notified. GBPI reserves the right of modification and final interpretation.

