

Heat Shrink Tester GBK-1



Introduction

It is used to determination of the degree of unrestrained linear thermal shrinkage and dimensional stability at different temperatures. Widely used in industries of plastic material, plastic products, petroleum, chemicals, research institute, inspection agency and so on.

Standard

ASTM D2732, GB/T 13519

Specification

Item	Technical parameters
Sample size	≤140×140mm
Temperature range	Room temperature~250°C
Temperature control accuracy	±0.1°C
Instrument size	340×400×220mm
Weight	13.5kg
Power	1500W
Power supply	AC 220V, 50Hz

Features

- High-quality aluminum alloy liquid tank and mask, good heat conduction and heat preservation effect.
- LCD display, display temperature and timing, convenient parameter setting and simple operation.

Product List

No.	Item		Remark	Quantity	
1	Power line		3*0.75 10A 1.8mts	1pc	
2	Cover		FS-1	1 pc	
3	Clamping net			lset	
4	Clamping net bracket			2 pcs	
5	Inner hexagon			1 pc	
6	Phillips screwdriver		6-10mm	1 pc	
7	Wooden box			1 pc	
2. Op	tional part				
No.	Item	Remark	Quantity		
1	Metrology certificate			Optional	
3. Use	er provided				
1	Power 500w 220V 10A, 3-hole socket, Ground wire				

Note: GBPI has always been committed to the innovation and improvement of product performance and function. For this reason, product technical specifications and appearance will also be changed accordingly. The above situation will not be notified. GBPI reserves the right of modification and final interpretation.



Distributed by: CN Technical Services Limited Call +44 (0)1354 699899 www.cntech.co.uk